

Package: icesDatras (via r-universe)

August 17, 2024

Version 1.4.2

Title DATRAS Trawl Survey Database Web Services

Imports utils

Suggests icesVocab

Description R interface to access the web services of the ICES
(International Council for the Exploration of the Sea) DATRAS
trawl survey database
<<https://datras.ices.dk/WebServices/Webservices.aspx>>.

License GPL (>= 2)

URL <https://datras.ices.dk/WebServices/Webservices.aspx>,
<https://github.com/ices-tools-prod/icesDatras>

BugReports <https://github.com/ices-tools-prod/icesDatras/issues>

RoxygenNote 7.3.1

Encoding UTF-8

Repository <https://ices-tools-prod.r-universe.dev>

RemoteUrl <https://github.com/ices-tools-prod/icesDatras>

RemoteRef HEAD

RemoteSha a1596faccd9215c4850774cc16de368c5649bdb4

Contents

checkSurveyOK	2
checkSurveyYearOK	3
checkSurveyYearQuarterOK	4
getCAdata	5
getCatchWgt	6
getCPUEAge	7
getCPUELength	8
getDATRAS	9
getDatrasDataOverview	10

getFlexFile	10
getHHdata	11
getHLdata	12
getIndices	13
getLTassessment	14
getSurveyList	15
getSurveyYearList	16
getSurveyYearQuarterList	16
icesDatras	17

Index	19
--------------	-----------

checkSurveyOK	<i>Check that a survey name is in the database</i>
---------------	--

Description

Checks a survey name against a list of all survey names in the DATRAS database. If the name is not matched it puts up a message showing the available survey names.

Usage

```
checkSurveyOK(survey)
```

Arguments

survey	the survey acronym, e.g. NS-IBTS.
--------	-----------------------------------

Value

logical.

See Also

[checkSurveyYearOK](#) and [getSurveyYearQuarterList](#) also perform checks against the DATRAS database.

[icesDatras-package](#) gives an overview of the package.

Examples

```
## Not run:
checkSurveyOK(survey = "ROCKALL")
checkSurveyOK(survey = "NOTALL")

## End(Not run)
```

checkSurveyYearOK	<i>Check that a survey and year combination is in the database</i>
-------------------	--

Description

Checks a year and/or survey name against a list of all survey year combinations in the DATRAS database. If the combination is not matched it puts up a message showing the available options.

Usage

```
checkSurveyYearOK(survey, year, checksurvey = TRUE)
```

Arguments

survey	the survey acronym, e.g. NS-IBTS.
year	the year of the survey, e.g. 2010.
checksurvey	logical, should the survey name also be checked.

Value

logical.

See Also

[checkSurveyOK](#) and [checkSurveyYearQuarterOK](#) also perform checks against the DATRAS database.
[icesDatras-package](#) gives an overview of the package.

Examples

```
## Not run:  
checkSurveyYearOK(survey = "ROCKALL", 2015)  
checkSurveyYearOK(survey = "ROCKALL", 2000)  
checkSurveyYearOK(survey = "NOTALL", 2000)  
  
## End(Not run)
```

`checkSurveyYearQuarterOK`*Check that a survey, year and quarter combination is in the database*

Description

Checks a quarter and/or year and/or survey name against a list of all survey year quarter combinations in the DATRAS database. If the combination is not matched it puts up a message showing the available options.

Usage

```
checkSurveyYearQuarterOK(  
  survey,  
  year,  
  quarter,  
  checksurvey = TRUE,  
  checkyear = TRUE  
)
```

Arguments

survey	the survey acronym, e.g. NS-IBTS.
year	the year of the survey, e.g. 2010.
quarter	the quarter of the year the survey took place, i.e. 1, 2, 3 or 4.
checksurvey	logical, should the survey name also be checked.
checkyear	logical, should the year also be checked.

Value

logical.

See Also

[checkSurveyOK](#) and [checkSurveyYearOK](#) also perform checks against the DATRAS database.
[icesDatras-package](#) gives an overview of the package.

Examples

```
## Not run:  
checkSurveyYearQuarterOK(survey = "ROCKALL", 2015, 3)  
checkSurveyYearQuarterOK(survey = "ROCKALL", 2015, 1)  
checkSurveyYearQuarterOK(survey = "ROCKALL", 2000, 1)  
checkSurveyYearQuarterOK(survey = "NOTALL", 2000, 1)  
  
# be careful of unexpected results with checksurvey and checkyear!  
checkSurveyYearQuarterOK(survey = "NOTALL", 2000, 1, checksurvey=FALSE)
```

```
## End(Not run)
```

getCAdata	<i>Get Age-Based Data</i>
-----------	---------------------------

Description

Get age-based data such as sex, maturity, and age counts per length of sampled species.

Usage

```
getCAdata(survey, year, quarter)
```

Arguments

survey	the survey acronym, e.g. NS-IBTS.
year	the year of the survey, e.g. 2010.
quarter	the quarter of the year the survey took place, i.e. 1, 2, 3 or 4.

Value

A data frame.

Author(s)

Colin Millar.

See Also

[getDATRAS](#) supports querying many years and quarters in one function call.

[getHHdata](#) and [getHLdata](#) get haul data and length-based data.

[icesDatras-package](#) gives an overview of the package.

Examples

```
## Not run:  
cadata <- getCAdata(survey = "ROCKALL", year = 2002, quarter = 3)  
str(cadata)  
  
## End(Not run)
```

`getCatchWgt`*Get Catch Weights*

Description

Calculate the total reported catch weight by species and haul.

Usage

```
getCatchWgt(survey, years, quarters, aphia)
```

Arguments

<code>survey</code>	the survey acronym e.g. NS-IBTS.
<code>years</code>	a vector of years of the survey, e.g. <code>c(2010, 2012)</code> or <code>2005:2010</code> .
<code>quarters</code>	a vector of quarters of the year the survey took place, e.g. <code>c(1, 4)</code> or <code>1:4</code> .
<code>aphia</code>	a vector of Aphia species codes defined in the WoRMS database, e.g. <code>c(126436, 1264374)</code> .

Value

A data frame.

Note

The `icesVocab` package provides `findAphia`, a function to look up Aphia species codes.

See Also

[getSurveyYearList](#), [getSurveyYearQuarterList](#), and [getDatrasDataOverview](#) also list available data.

[icesDatras-package](#) gives an overview of the package.

Examples

```
## Not run:
getCatchWgt(survey = "ROCKALL", years = 2002, quarters = 3, aphia = 126437)

# look up specific species
aphia <- icesVocab::findAphia(c("cod", "haddock"))
cwt <- getCatchWgt(survey = "ROCKALL", years = 2002, quarters = 3, aphia = aphia)

## End(Not run)
```

getCPUEAge	<i>Get CPUE per Age per Haul per Hour for a given Survey, year and Quarter</i>
------------	--

Description

Get CPUE per Age per Haul per Hour for a given Survey, year and Quarter

Usage

```
getCPUEAge(survey, year, quarter)
```

Arguments

survey	the survey acronym, e.g. NS-IBTS.
year	the year of the survey, e.g. 2010.
quarter	the quarter of interest, e.g. 1

Value

A data frame.

Author(s)

Adriana Villamor.

See Also

[getHHdata](#) and [getCAdata](#) get haul data and age-based data., and [getIndices](#), and [getCPUELength](#).
[icesDatras-package](#) gives an overview of the package.

Examples

```
## Not run:  
getCPUEperAge(survey = "NS-IBTS", year = 2018, quarter = 1)  
  
## End(Not run)
```

getCPUELength	<i>Get CPUE per Length per Haul per Hour for a given Survey, year and Quarter</i>
---------------	---

Description

Get CPUE per Length per Haul per Hour for a given Survey, year and Quarter

Usage

```
getCPUELength(survey, year, quarter)
```

Arguments

survey	the survey acronym, e.g. NS-IBTS.
year	the year of the survey, e.g. 2010.
quarter	the quarter of interest, e.g. 1

Value

A data frame.

Author(s)

Adriana Villamor.

See Also

[getHHdata](#) and [getCAdata](#) get haul data and age-based data., and [getIndices](#), and [getCPUEAge](#).
[icesDatras-package](#) gives an overview of the package.

Examples

```
## Not run:  
getCPUELength(survey = "NS-IBTS", year = 2018, quarter = 1)  
  
## End(Not run)
```

`getDATRAS`*Get Any DATRAS Data*

Description

This function combines the functionality of `getHHdata`, `getHLdata`, and `getCAdata`. It supports querying many years and quarters in one function call.

Usage

```
getDATRAS(record = "HH", survey, years, quarters)
```

Arguments

<code>record</code>	the data type required: "HH" haul data, "HL" length-based data, "CA" age-based data.
<code>survey</code>	the survey acronym e.g. NS-IBTS.
<code>years</code>	a vector of years of the survey, e.g. <code>c(2010, 2012)</code> or <code>2005:2010</code> .
<code>quarters</code>	a vector of quarters of the year the survey took place, i.e. <code>c(1, 4)</code> or <code>1:4</code> .

Value

A data frame.

Author(s)

Scott Large and Colin Millar.

See Also

[getHHdata](#), [getHLdata](#), and [getCAdata](#) get haul data, length-based data, and age-based data.
[icesDatras-package](#) gives an overview of the package.

Examples

```
## Not run:  
hhdata <- getDATRAS(record = "HH", survey = "ROCKALL", years = 2002, quarters = 3)  
hlldata <- getDATRAS(record = "HL", survey = "ROCKALL", years = 2002, quarters = 3)  
cadata <- getDATRAS(record = "CA", survey = "ROCKALL", years = 2002, quarters = 3)  
  
## End(Not run)
```

getDatrasDataOverview *Summarize Data Availability*

Description

Evaluate a presence-absence table for each survey with '1' where there is data and '0' (printed as '.') otherwise.

Usage

```
getDatrasDataOverview(surveys = NULL, long = TRUE)
```

Arguments

surveys a vector of survey names, or NULL to process all surveys.
 long whether tables should have year as row names (default) or column names.

Value

A list of tables.

See Also

[getSurveyList](#), [getSurveyYearList](#), and [getSurveyYearQuarterList](#) also list available data.
[icesDatras-package](#) gives an overview of the package.

Examples

```
## Not run:
getDatrasDataOverview(surveys = "ROCKALL", long = FALSE)

## End(Not run)
```

getFlexFile *Get Flex File*

Description

Get all information in HH plus estimates of Door Spread, Wing Spread and Swept Area per square km. Only available for NS-IBTS survey.

Usage

```
getFlexFile(survey, year, quarter)
```

Arguments

survey	the survey acronym, e.g. NS-IBTS.
year	the year of the survey, e.g. 2010.
quarter	the quarter of the year the survey took place, i.e. 1, 2, 3 or 4.

Value

A data frame.

Author(s)

Adriana Villamor.

See Also

[getDATRAS](#) supports querying many years and quarters in one function call.

[getHHdata](#) get haul data

[icesDatras-package](#) gives an overview of the package.

Examples

```
## Not run:
flex <- getFlexFile(survey = "NS-IBTS", year = 2020, quarter = 1)
str(flex)

# error checking examples:
flex <- getFlexFile(survey = "NS-IBTS", year = 2016, quarter = 1)
flex <- getFlexFile(survey = "NS-IBTS", year = 2030, quarter = 1)
flex <- getFlexFile(survey = "NS-IBTS", year = 2016, quarter = 6)

## End(Not run)
```

getHHdata

Get Haul Data

Description

Get haul data such as position, depth, sampling method, etc.

Usage

```
getHHdata(survey, year, quarter)
```

Arguments

survey	the survey acronym, e.g. NS-IBTS.
year	the year of the survey, e.g. 2010.
quarter	the quarter of the year the survey took place, i.e. 1, 2, 3 or 4.

Value

A data frame.

Author(s)

Colin Millar.

See Also

[getDATRAS](#) supports querying many years and quarters in one function call.

[getHLdata](#) and [getCAdata](#) get length-based data and age-based data.

[icesDatras-package](#) gives an overview of the package.

Examples

```
## Not run:
hhdata <- getHHdata(survey = "ROCKALL", year = 2002, quarter = 3)
str(hhdata)

# error checking examples:
hhdata <- getHHdata(survey = "NS_IBTS", year = 2016, quarter = 1)
hhdata <- getHHdata(survey = "NS-IBTS", year = 2030, quarter = 1)
hhdata <- getHHdata(survey = "NS-IBTS", year = 2016, quarter = 6)

## End(Not run)
```

getHLdata

Get Length-Based Data

Description

Get length-based information such as measured length, individual counts, and sub-factors of sampled species.

Usage

```
getHLdata(survey, year, quarter, species)
```

Arguments

survey	the survey acronym, e.g. NS-IBTS.
year	the year of the survey, e.g. 2010.
quarter	the quarter of the year the survey took place, i.e. 1, 2, 3 or 4.
species	the valid aphia code of the species to download, if NULL all species are included

Value

A data frame.

See Also

[getDATRAS](#) supports querying many years and quarters in one function call.

[getHHdata](#) and [getCAdata](#) get haul data and age-based data.

[icesDatras-package](#) gives an overview of the package.

Examples

```
## Not run:  
hldata <- getHLdata(survey = "BTS", year = 1993, quarter = 3, species = 105883)  
str(hldata)  
  
## End(Not run)
```

getIndices

Get Survey Indices

Description

Get age based indices of abundance by species, survey and year.

Usage

```
getIndices(survey, year, quarter, species)
```

Arguments

survey	the survey acronym, e.g. NS-IBTS.
year	the year of the survey, e.g. 2010.
quarter	the quarter of the year the survey took place, i.e. 1, 2, 3 or 4.
species	the aphia species code for the species of interest.

Value

A data frame.

Note

The **icesAdvice** package provides `findAphia`, a function to look up Aphia species codes.

See Also

[getDATRAS](#) supports querying many years and quarters in one function call.

[getHHdata](#) and [getCAdata](#) get haul data and age-based data.

[icesDatras-package](#) gives an overview of the package.

Examples

```
## Not run:
haddock_aphia <- icesVocab::findAphia("haddock")
index <- getIndices(survey = "NS-IBTS", year = 2002, quarter = 3, species = haddock_aphia)
str(index)

## End(Not run)
```

getLTassessment

Get Litter assessment output

Description

Get Litter assessment output by survey, year and quarter. The raw data are also included in this file.

Usage

```
getLTassessment(survey, year, quarter)
```

Arguments

survey	the survey acronym, e.g. NS-IBTS.
year	the year of the survey, e.g. 2010.
quarter	the quarter of the year the survey took place, i.e. 1, 2, 3 or 4.

Value

A data frame.

Note

The **icesAdvice** package provides `findAphia`, a function to look up Aphia species codes.

See Also

[getDATRAS](#) supports querying many years and quarters in one function call.

[getHHdata](#) and [getCAdata](#) get haul data and age-based data.

[icesDatras-package](#) gives an overview of the package.

Examples

```
## Not run:  
index <- getLTassessment(survey = "NS-IBTS", year = 2002, quarter = 3)  
str(index)  
  
## End(Not run)
```

getSurveyList	<i>Get a List of All Surveys</i>
---------------	----------------------------------

Description

Get a list of all survey acronyms.

Usage

```
getSurveyList()
```

Value

A character vector.

Author(s)

Colin Millar.

See Also

[getSurveyYearList](#), [getSurveyYearQuarterList](#), and [getDatrasDataOverview](#) also list available data.

[icesDatras-package](#) gives an overview of the package.

Examples

```
## Not run:  
getSurveyList()  
  
## End(Not run)
```

`getSurveyYearList` *Get a List of Survey Years*

Description

Get a list of all data years for a given survey.

Usage

```
getSurveyYearList(survey)
```

Arguments

`survey` the survey acronym, e.g. NS-IBTS.

Value

A numeric vector.

Author(s)

Colin Millar.

See Also

[getSurveyList](#), [getSurveyYearQuarterList](#), and [getDatrasDataOverview](#) also list available data.

[icesDatras-package](#) gives an overview of the package.

Examples

```
## Not run:  
getSurveyYearList(survey = "ROCKALL")  
  
## End(Not run)
```

`getSurveyYearQuarterList`
Get a List of Quarters

Description

Get a list of quarters available for a given survey and year.

Usage

```
getSurveyYearQuarterList(survey, year)
```


Arguments

survey the survey acronym, e.g. NS-IBTS.
 year the year of the survey, e.g. 2010.

Value

A numeric vector.

Author(s)

Colin Millar.

See Also

[getSurveyYearList](#), [getSurveyYearQuarterList](#), and [getDatrasDataOverview](#) also list available data.

[icesDatras-package](#) gives an overview of the package.

Examples

```
## Not run:
getSurveyYearQuarterList(survey = "ROCKALL", year = 2002)

## End(Not run)
```

 icesDatras

DATRAS Trawl Survey Database Web Services

Description

R interface to access the web services of the ICES DATRAS trawl survey database.

Details

Exchange data:

getHHdata	haul data
getHLdata	length-based data
getCadata	age-based data
getDATRAS	exchange data

Catch weights:

getCatchWgt	catch weights
-----------------------------	---------------

Survey indices:

`getIndices` survey indices

Overview of available data:

<code>getSurveyList</code>	surveys
<code>getSurveyYearList</code>	years
<code>getSurveyYearQuarterList</code>	quarters
<code>getDatrasDataOverview</code>	surveys, years, and quarters

Basic queries (thin web service wrappers):

`getCAdata`, `getHHdata`, `getHLdata`, `getIndices`, `getSurveyList`, `getSurveyYearList`, `getSurveyYearQuarterList`

Derived queries (combining web services with R computations):

`getCatchWgt`, `getDatrasDataOverview`, `getDATRAS`

Author(s)

Colin Millar, Scott Large, and Arni Magnusson.

References

ICES DATRAS database: <http://datras.ices.dk>.

ICES DATRAS web services: <https://datras.ices.dk/WebServices/Webservices.aspx>.

Index

[checkSurveyOK](#), [2](#), [3](#), [4](#)
[checkSurveyYearOK](#), [2](#), [3](#), [4](#)
[checkSurveyYearQuarterOK](#), [3](#), [4](#)

[getCAdata](#), [5](#), [7–9](#), [12–14](#), [17](#)
[getCatchWgt](#), [6](#), [17](#)
[getCPUEAge](#), [7](#), [8](#)
[getCPUELength](#), [7](#), [8](#)
[getDATRAS](#), [5](#), [9](#), [11–14](#), [17](#)
[getDatrasDataOverview](#), [6](#), [10](#), [15–18](#)
[getFlexFile](#), [10](#)
[getHHdata](#), [5](#), [7–9](#), [11](#), [11](#), [13](#), [14](#), [17](#)
[getHLdata](#), [5](#), [9](#), [12](#), [12](#), [17](#)
[getIndices](#), [7](#), [8](#), [13](#), [18](#)
[getLTassessment](#), [14](#)
[getSurveyList](#), [10](#), [15](#), [16](#), [18](#)
[getSurveyYearList](#), [6](#), [10](#), [15](#), [16](#), [17](#), [18](#)
[getSurveyYearQuarterList](#), [2](#), [6](#), [10](#), [15](#), [16](#),
[16](#), [17](#), [18](#)

[icesDatras](#), [17](#)
[icesDatras-package \(icesDatras\)](#), [17](#)